

SPECIFICATION OVERVIEWS

Model	PAE-11 CUB
Max Power	350W
Top Designed Speed	12.4 KM/H

MOTOR & BATTERY

Motor Type	MY1016Z
Starting Mode	Electric
MAXIMUM SPEED	2650~2950r/min
Rated Voltage	24V
Rated Current	18.7A
Battery	24V/7A
Charging Time	8H

TRANSMISSION

PRIMARY DRIVE SYSTEM	Chain
----------------------	-------

CHASSIS

Frame	Steel frame
Swing Arm	Steel fork L=300mm
Axle Base(mm)	680/26.78in
Chain	T8F 78L
Sprockets	25/45

BRAKE & SUSPENSIONS

Brake Operation Mode-Front	Pull-brake mechanical system
Brake Operation Mode-Rear	Pull-brake mechanical system
Shock Absorber-Front	/
Shock Absorber-Rear	Ordinary steel shock L=140
Tyer Type-Front	Road tire 13*5.00-6
Tyer Type-Rear	Road tire 13*5.00-6
Tyer Pressure-Front	24psi
Tyer Pressure-Rear	24psi
Rim Type-Front	Steel rim 6"
Rim Type-Rear	Steel rim 6"

ELECTRIC COMPONENTS

Controller	Brush
Cooling Mode	Natural air cooling
Rated Voltage	24V
Current Protection	19A
Undervoltage Protection	21±1V

DIMENSIONS

Endurance Mileage	5.27 KM
-------------------	---------



Seat Height	500mm/19.7in
Handlebar Height	695mm/27.4in
Turning Circle Diameter	2.2m
Wheel Base	680mm/26.7in
Ground Clearance	75mm/2.95in
Weight Capacity	50kg/110 lbs
Max Limp Angle	30°
Bike Size	1010×575×695mm(39.8*22.7*27.4in)
Packing Size	1020×570×500mm(40.2*22.4*19.9in)
Net Weight	39kg/86lbs
Shipping Weight	45kg/99lbs
Max Load	50kg/110lbs